

Braunschweig Civil Engineering Materials Testing Institute (MPA Braunschweig)

Beethovenstr. 52, DE-38106 Braunschweig, Germany Tel: ++49(0)531-391-5400 Fax: ++49(0)531-391-5900 Email: info@mpa.tu-bs.de Website: www.mpa.tu-bs.de

This certificate of compliance validates the following

TEST REPORT NUMBER: DATE OF ISSUE:

3478/549/14 2015-02-02

CERTIFICATE NUMBER: DATE OF ISSUE:

MPA BS-Z-047/16 2021-02-08

2026-02-07

DATE OF EXPIRY:

N/A

DATE OF EXPIRY:

CERTIFICATION

NAME OF FACTORY/ MANUFACTURER:

Rosenberg Ventilatoren GmbH

BRAND:

PRODUCT:

Rosenberg Fans

MARK:

FACTORY ADDRESS/REGION:

Tel: +49 (0) 7940/142-0 Fax: +49 (0) 7940/142-125

gmbh.com

NAME OF THE

LOGO ON THE

MODEL/NO:

ANS F400 or ANBB F400

Maybachstrasse 1

D-74676 Künzelsau-Gaisbach

Germany

Email: info@rosenberg-

DESCRIPTION OF THE

PRODUCT:

Powered fans to be used for exhausting smoke and heat from buildings in case of fire. Such fans create smoke free areas making it easier for people to leave and for the fire fighters to enter the building. For smoke control purposes powered fans can also be used for staircase pressurization.

TEST STANDARD:

EN 12101-3/AC:2005, ISO 21927-3:2006-11

TEST DESCRIPTION:

Two smoke and heat exhaust ventilators with nominal diameters of 630 mm and 1,250 mm have been tested in a furnace at a temperature of 400°C. The fans have maintained their function for about 135 min including a restart at after power off for 2 min.

SPECIFICATION OF TEST SPECIMEN:

The fans were tested mounted horizontally and vertically in a furnace. They may be used for

both functions.

TEST RESULT:

MAINTENANCE OF FUNCTION INTERPRETATION **RESULT** 400°C FOR 120 MIN SUCCESSFUL PASS

NAME OF TEST FACILITY:

MPA Braunschweig

TEST FACILITY

Beethovenstr. 52, D-38106 Braunschweig

Tel: ++49(0) 531 391 5400, Fax: ++49(0) 531 391 5900

ADDRESS/REGION:

Email: info@mpa.tu-bs.de, Website: www.mpa-tu-bs.de

PRODUCT APPLICATION

GUIDELINE (END USE):

The fan should be mounted horizontally or vertically inside or outside the fire zone or outside of a building without thermal insulation. In case of fire, it can be used to exhaust smoke and heat but it may also be part of a general ventilation system.

Range of diameters: F400(120) 400 mm ... 2,000 mm

Draing. W. Hinrichs SIGNED BY: Head of certification

The above certificate is valid only when installed in accordance with the 'Product Application Guideline (End Use)'. To verify the validity of the product please log into our website, click on 'others' and then on 'certificates'. You will find a list of manufacturers and a certificate with the number as given above.



Braunschweig Civil Engineering Materials Testing Institute (MPA Braunschweig)

Beethovenstr. 52, DE-38106 Braunschweig, Germany Tel: ++49(0)531-391-5400 Fax: ++49(0)531-391-5900 Email: info@mpa.tu-bs.de Website: www.mpa.tu-bs.de

ACCREDITED BY:

DAkkS

AS PER:

ISO/IEC 17065

VALIDITY:

N/A

REFERENCE NUMBER:

D-ZE-11267-01-00

DAkkS

ISO/IEC 17025

N/A

D-PL-11267-01-02

THE LIST OF ACCREDITED TESTS (FIRE AND LIFE SAFETY PRODUCTS ONLY)

TEST STANDARD	TITLE
EN 12101-1	Smoke and heat control systems –
	Part 1: Specification for smoke barriers
EN 12101-2	Smoke and heat control systems
	Part 2: Specification for natural smoke and heat exhaust ventilators
EN 12101-3	Smoke and heat control systems –
	Part 3: Specification for powered smoke and heat exhaust ventilators
EN 12101-6	Smoke and heat control systems –
	Part 6: Specification for pressure differential systems, Kits
EN 12101-7	Smoke and heat control systems –
	Part 7: Smoke duct sections
EN 12101-8	Smoke and heat control systems –
	Part 8: Smoke control dampers
EN 1366-8	Fire resistance tests for service installations –
	Part 8: Smoke extraction ducts
EN 1366-9	Fire resistance tests for service installations –
	Part 9: Single compartment smoke extraction ducts
EN 1366-10	Fire resistance tests for service installations –
	Part 10: Smoke control dampers
EN 13501-4	Fire classification of construction products and building elements –
	Part 4: Classification using data from fire resistance tests on components of smoke control systems
	E MPA
	BS / BS
	10

aunschwell